

# belluno bibs (bed-in-bed system)

With bed insert everywhere at home

# Specifications - belluno bibs (Bed-in-bed system)

Total weight: approx. 65 kg

Lying surface dimension:  $90/100^{1} \times 190 \text{ or } 200 \text{ cm}$ 

Nominal dimension: 89 x 187/197 cm

Safe working load: 200 kg

Maximum person weight: 165 kg

Height adjustment: 31 – 75 cm

Lifter space: 11 cm

Special dimensions: 80 – 140 cm width

180 – 220 cm length

#### Motors

Water-resistant to IPX4, high quality spiral cable with pull relief and anti-kink device, as well as a safety extra-low voltage system.


### Features

# Art.-No.

282 90/100 x 190 cm 282 90/100 x 200 cm


Subject to technical modification.





Base in a lenth of 1240 mm (Only upon request)

Transport system for belluno bibs



Base in a length of 1560 mm, standard base width

#### 4-section

Electrical adjustment of the lying surface including the automatic triple knee break action.

#### **Basic equipment:**

Safety extra-low voltage system Wooden slats

Provided feet with balance screw for free standing assembly Mattress brackets for width extension

#### Extras:

Leg position parallel to lying surface with 90° end position Wooden slats with tension regulation

Higher feet to increase the height by approx. 4 cm

Mattress compensation

Integrated head rest for 5-section lying surface

ripolux® neo- spring lying surface system incl. mattress compensation

Steel lying surface with removable bars

Mattress bracket on the foot end

#### Accessories:

Lifting pole with hand grip Companion bed 90/100 cm width (wood work only) Bed lamps

Foot bar 190 cm for 90 cm width (to extend to 200 cm)

Foot bar 200 cm for 90 cm width (to shorten to 190 cm)

Infusion holder

Mattresses

Side rail bumpers

Side rails for bed insert, 100 cm fitting

Side rails for bed insert, 90 cm fitting

Transport and storage system

# Safety guarantees:

- Primary fuse in the power plug
- Secondary fuse/polyswitch
- Thermal release
- Locking function on the hand control
- Hand control with single faulty safety
- Special spiral mains cable
- Pull relief at power plug and anti-kink device
- Water-resistant to IPX4





<sup>&</sup>lt;sup>1</sup> With the aid of the mattress bracket extentable in width.