

FEAL

...improving life



Portable ramps

Fixed, folding or telescopic. Our portable ramps are available in a variety of sizes and designs. Easy to take with you on trips or to places where there are no fixed ramps. With handles that are easy to fold up, a simple lock that you can open and close with one hand and excellent slip resistance.

All our portable ramps have a side profile of 52 mm/2,0 inches in height, apart from FL 110, FL 150 and FL 200 which have 35 mm/1,4 inches. In these instances, the side profile also works as a handle.

Fixed ramps



Our fixed ramps are available in multiple sizes to suit all needs.

| | Length (cm/in) | Weight (kg/lb) | Max. load (kg/lb) | Inside width (cm/in) | Recommended max. height (cm/in) |
|-------|----------------|----------------|-------------------|----------------------|---------------------------------|
| X050 | 55/22 | 1,5/3,3 | 200/440 | 21/8 | 10/4 |
| X100 | 116/46 | 3,1/6,8 | 200/440 | 21/8 | 20/8 |
| XW100 | 106/42 | 3,5/7,7 | 200/440 | 27/11 | 20/8 |

Telescopic ramps



Our telescopic ramps are available in multiple lengths so that they can be used in many different environments.

| | Length (cm/in) | Weight (kg/lb) | Max. load (kg/lb) | Inside width (cm/in) | Recommended max. height (cm/in) | Folded length (cm/in) |
|--------|----------------|----------------|-------------------|----------------------|---------------------------------|-----------------------|
| T090 | 90/35 | 2,8/6,1 | 200/440 | 19/7 | 20/8 | 58/23 |
| T120 | 119/47 | 3,7/8,1 | 200/440 | 19/7 | 25/10 | 75/30 |
| T200 | 202/80 | 5,6/12,3 | 150/330 | 19/7 | 40/16 | 116/46 |
| T200-3 | 199/78 | 6,5/14,3 | 150/330 | 17/7 | 40/16 | 87/34 |
| T300 | 288/113 | 8,2/18,0 | 125/275 | 17/7 | 60/24 | 116/46 |

Folding ramps



Our folding ramps are easy to take with you and are available in several different sizes to suit all needs.

| | Length (cm/in) | Weight (kg/lb) | Max. load (kg/lb) | Inside width (cm/in) | Recommended max. height (cm/in) | Folded length (cm/in) |
|-------|----------------|----------------|-------------------|----------------------|---------------------------------|-----------------------|
| F110 | 110/43 | 3,8/8,3 | 200/440 | 21/8 | 20/8 | 57/22 |
| F150 | 150/59 | 4,9/10,8 | 200/440 | 21/8 | 30/12 | 76/30 |
| F200 | 200/79 | 6,3/13,9 | 150/330 | 21/8 | 40/16 | 101/40 |
| FL110 | 110/43 | 2,3/5,1 | 200/440 | 18/7 | 20/8 | 56/22 |
| FL150 | 150/59 | 3,4/7,5 | 200/440 | 18/7 | 30/12 | 76/30 |
| FL200 | 200/79 | 6,0/13,2 | 150/330 | 18/7 | 40/16 | 101/40 |
| FW200 | 212/83 | 8,0/17,6 | 150/330 | 27/11 | 40/16 | 107/42 |

Folding telescopic ramps



Our folding telescopic ramps can be used in many different environments. They are easy to fold up and transport.

| | Length (cm/in) | Weight (kg/lb) | Max. load (kg/lb) | Inside width (cm/in) | Recommended max. height (cm/in) | Folded length (cm/in) |
|--------|----------------|----------------|-------------------|----------------------|---------------------------------|-----------------------|
| FTW200 | 205/81 | 8,3/18,3 | 150/330 | 25/10 | 40/16 | 77/30 |
| FTW300 | 295/116 | 11,4/25,1 | 125/275 | 25/10 | 60/24 | 107/42 |
| FT200 | 201/79 | 6,8/15,0 | 150/330 | 19/7 | 40/16 | 76/30 |
| FT300 | 276/109 | 8,6/19,0 | 125/275 | 19/7 | 60/24 | 101/40 |

Anyramp



Our light and non-slip portable loading ramps, Anyramp, are suitable for a range of different applications. You fold them up with one easy manoeuvre.

| | Length (cm/in) | Weight (kg/lb) | Max. load (kg/lb) | Inside width (cm/in) | Folded length (cm/in) |
|---------|----------------|----------------|-------------------|----------------------|-----------------------|
| VR10 | 100/39 | 11/24,2 | 400/880 | 82/32 | 52/20 |
| VR10-1* | 100/39 | 10/22,0 | 400/880 | 82/32 | 100/39 |
| VR16 | 160/63 | 18/39,6 | 400/880 | 82/32 | 85/33 |
| VR20 | 200/79 | 21/46,3 | 400/880 | 82/32 | 105/41 |
| VR25 | 250/98 | 25/55,1 | 400/880 | 82/32 | 130/51 |
| VR28 | 279/110 | 29/63,9 | 400/880 | 82/32 | 145/57 |

* One-piece ramp.

iRamp Portable



iRAMP®
PORTABLE

IRP is a new portable ramp which folds lengthways. It provides a full surface required for things such as electric wheelchairs and three-wheeled scooters. It is very lightweight, made from a durable material and is capable of supporting heavy loads.

The IRP ramps are only 5.5 cm/2,2 inches thick when folded up.

| | Length (cm/in) | Weight (kg/lb) | Max. load (kg/lb) | Inside width (cm/in) | Recommended max. height (cm/in) |
|--------|----------------|----------------|-------------------|----------------------|---------------------------------|
| IRP050 | 52/20 | 3,8/8,4 | 400/880 | 76/30 | 10/4 |
| IRP090 | 92/36 | 6,5/14,3 | 400/880 | 76/30 | 18/7 |
| IRP120 | 116/46 | 8,7/19,2 | 400/880 | 76/30 | 24/9 |
| IRP150 | 150/59 | 10/22,0 | 400/880 | 76/30 | 34/13 |
| IRP170 | 167/66 | 12,5/27,5 | 400/880 | 76/30 | 34/13 |
| IRP200 | 200/79 | 14,7/32,4 | 400/880 | 76/30 | 40/16 |

iRamp Carbon



| | Length (cm/in) | Weight (kg/lb) | Max. load (kg/lb) | Inside width (cm/in) | Recommended max. height (cm/in) |
|--------|----------------|----------------|-------------------|----------------------|---------------------------------|
| IRC075 | 75/30 | 2,6/5,7 | 250/550 | 75/30 | 15/6 |
| IRC120 | 120/47 | 3,9/8,6 | 250/550 | 75/30 | 25/10 |
| IRC150 | 150/59 | 5/11,0 | 250/550 | 75/30 | 30/12 |
| IRC200 | 200/79 | 6,8/15,0 | 250/550 | 75/30 | 40/16 |